4-WHEEL SCOOTER



ENGINEERED FOR POWERFUL PERFORMANCE AND EXCEPTIONAL STYLE

The **Pursuit® XL** is an exciting blend of power and precision that features full suspension, low-profile tires and a hydraulic-sealed brake system. Standard luxury touches like a wraparound delta tiller and LED lighting make it the ultimate outdoor scooter.







Full Suspension

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

SPECIFICATIONS

PURSUIT® XL	4-wheel	Model # SC714
Weight capacity:	400 lbs.	
Maximum speed ¹ :	Up to 8.5 mph	1
Ground clearance ² :	5.25"	
Turning radius:	82.5"	
Overall length ² :	56.25"	
Overall width ² :	27.25"	
Front tires:	13" pneumatic	
Rear tires:	13" pneumatic	
Suspension:	Front and Rea	ar
Range per charge ¹ :	Group 24 (70 AH): Up to 22.51 miles Group 27 (100 AH): Up to 29.51 miles	
Total weight without batteries:	205.5 lbs. (without seat or batteries)	
Heaviest piece when disassembled:	N/A	
Standard seating:	Type: Reclining, pillow top, high-back seat with sliders Weight: 48 lbs. Material: Black Vinyl Dimensions: 19.5" x 17.5"	
Drive system:	Rear-wheel di	rive, sealed transaxle, 24-volt DC motor
Brakes:	Regenerative and electromechanical	
Battery requirements ³ :	(2) 12-volt, deep cycle Size: Group 24 (70 AH), Group 27 (100 AH) Weight ⁴ : Group 24: 55 lbs. each, Group 27: 60.5 lbs. each	
Battery charger:	8-amp, off-box	ard

FEATURES

- Infinitely-adjustable tiller angle with conveniently located handle
- Powerful drivetrain; features 180 amp microprocessor-based controller
- Deluxe reclining high-back seat with headrest and sliders
- Full lighting package that includes directional signals and lower headlight
- Delta tiller with wraparound handles
- Large 13" low-profile, pneumatic tires for excellent outdoor performance
- Front and rear suspension
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- · Rearview mirror standard
- Hydraulic handbrake

OPTIONS

- Rear basket
- Safety flag
- Durable weather cover

Color:





Silver

Red

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- 3 AGM or gel cell type required.
- 4 Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or – 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.



