

1



photo courtesy of Mobility Elevator & Lift Co.

2



3



4

Savaria® Multilift Vertical Platform Lift

VALUE AND RELIABILITY

Multilift models can be customized with a variety of options for gates, doors and automatic operation. All lifts use constant pressure operation with controls onboard the lift, as well as a self-supporting base and tower structure that houses mechanical components keeping them protected and making for simplicity of installation.

① Enclosure: This unit is fully enclosed with aluminum. Glass or acrylic inserts can be added, as well as a domed, ventilated roof. Suitable for an outdoor application to protect the user from the weather, this lift is also ideal for indoor applications with its self-supporting tower. Shipped partially assembled, this unit features easy installation with anchorage to a concrete pad the only required construction for installation.

② Mobile: Not restricted by permanent construction, this unit can be moved to provide accessibility where and when you need it.

③ 3G/Three Gate: The Multilift 3-gate system is ideal for stages or other applications where a full enclosure is not desirable due to construction concerns or because a full enclosure would obstruct the surrounding view. The fixed side walls and landing gate create a partial enclosure for complete safety when the lift is in use, with minimal obstruction and no construction required.

④ Standard: For basic deck or porch access, choose the standard model. It's up for the challenge of tough climate conditions. The standard unit travels up to 72" with 2 stops and offers a choice of platform sizes.

Savaria® Multilift Vertical Platform Lift

VALUE AND RELIABILITY

SPECIFICATIONS BY MODEL

	Standard	Enclosure	Mobile [†]	3G [†]
Standard platform sizes	34" x 48" 34" x 54" 34" x 60" (86.4 cm x 121.9 cm) (86.4 cm x 137.1 cm) (86.4 cm x 152.4 cm) 36" width platform O	36" x 48" 36" x 54" 36" x 60" (91.4 cm x 121.9 cm) (91.4 cm x 137.1 cm) (91.4 cm x 152.4 cm)	36" x 48" (91.4 cm x 121.9 cm)	36" x 54" (91.4 cm x 137.1 cm) 36" x 48" O 36" x 60" O (91.4 cm x 121.9 cm) (91.4 cm x 152.4 cm)
Maximum travel	48" (121.9 cm) S 72" (182.9 cm) O	48" (121.9 cm) S 72" (182.9 cm) O	48" (121.9 cm)	48" (121.9 cm)
Enclosure type	None	Full	None	Partial
Platform gates	All optional*	N/A	2	1
Landing gates/doors	All optional*	Lower landing door S All others optional*	N/A	Lower and upper landing gates S
Automated options	Swing door, platform gate operator	Door or gate operator (upper landing), door operator (lower landing)	None	Gate operator (upper landing)
Access Ramp	Auto S Fixed O	Fixed O	Auto S	Fixed O
Motor	1 hp	1 hp	1 hp	1 hp
Power	110 AC S 220 AC 24 V battery back-up O	110 AC S 220 AC 24 V battery back-up O	110 AC 24 V battery back-up O	110 AC 24 V battery back-up O
Finish	Beige powdercoat S Glass, acrylic door or gate inserts O Custom colour O	Beige powdercoat S Glass, acrylic door or gate inserts O Custom colour O	Beige powdercoat S	Beige powdercoat S Custom colour O
Capacity	750 lbs (340 kg)			
Speed	8 ft per minute			
Warranty	3-year parts warranty, see dealer for more details			

S-Standard, O-Optional

[†]90° platform not available

*aluminum door(s), fire rated Pro auto or manual door, flush wooden door

The Multilift complies with ASME A18.1 (US), and B.355 & B.613 (Canada).

For drawings, detailed specifications and a complete list of options for your Savaria Multilift vertical platform lift, consult your local authorized Savaria dealer. To locate a dealer near you, visit savaria.com, or call us.

**Talk to a Savaria dealer about
how the Multilift can give you
the access you need.**

Authorized Savaria dealer:

 **savaria**

www.savaria.com

2 Walker Drive, Brampton, ON L6T 5E1 Canada

tel: 800.661.5112 fax: 905.791.2222