

SUPERIOR PERFORMANCE!

Having launched the first mid-wheel drive platform to the wheelchair market nearly 30 years ago, Permobil honors that rich tradition with the addition of the M300 to its product line. Developed by Permobil Senior Designers, Mehdi Mirzaie and Bo Engman, the M300 features the groundbreaking, patent-pending Climbing and Traction Link system. With its compact size, the M300 has a tight 20" turning radius, comes with PG 120 amp R-Net electronics and offers two speed packages-6 MPH standard and 7.5 MPH optional. The M300 also features stylish easy-to-replace swing arm covers made of scratch resistant material, which protect the swing arms from unsightly chips and scrapes. Easy to maintain, the M300 provides quick access to components and requires no special tools for servicing

M300



CATLINK SUSPENSION

Casters are connected for added climbing stability.

ADVANCED SHOCK DESIGN

Easily adjusted to provide a comfortable ride for any user.

TIGHT TURNING RADIUS

20" / 510 mm turning radius for increased maneuverability.

FRONT AND REAR TIE-DOWNS

Safety is first both in and out of the vehicle!

















AVAILABLE SHROUD COLORS





DIGITAL ARMY CAMO







REALTREE AP CAMO



permobil

AVAILABLE SHROUD COLORS

Maximum User Weight	300 lbs	136 kg
Maximum Speed Options	6 MPH, 7.5 MPH	10 km/h, 12 km/h
Driving Range ¹	13 miles	21 km
Base Width	24"	615 mm
Base Length	36.5"	925 mm
Minimum Turning Radius	20"	510 mm
Ground Clearance	3″	75 mm
Optional Seat Elevator	8"	200 mm
Battery Type	Group 24, Group 34	
Drive Electronics	120A R-net	
Maximum Slope ²	9° Up / 9° Down	

I ACTUAL DRIVING RANGE WILL VARY BASED ON DRIVING AND BATTERY CONDITIONS. 2 REFER TO OWNER MANUAL FOR SAFE DRIVING PRACTICES

PH: 800.736.0925 | FAX: 800.231.3256

Seat to Floor Height	(Elevator)	17.5"	445 mm
	(Seat Tube)	17.5", 18.25", 19"	445, 465, 485 mm
Tilt Options	(Power)	0° – 50°	
	(Power)	-5° – 45°	
Recline Options	(Power)	85° – 175°	
	(Manual)	85° – 120°	
Legrest Elevation Options	(Power)	85° – 170°	
	(Manual)	85° – 170°	
Armrest Pad Lengths		10", 13", 16"	260, 335, 410 mm
Seat Widths		17", 19", 21", 23"	420, 470, 520, 570 mm
Seat Depths		14" - 22"	370 — 570 mm
Backrest Heights		20", 23" – 28"	500, 570 – 710 mm