



FORTRESS® OSHA Stair System

Technical Specifications

MODEL	FOR2334	FOR2742
NUMBER OF RISERS	3	4
HEIGHT ADJUSTMENT	23", 25½", & 34"	27½", 34", & 42½"
OSHA COMPLIANT HEIGHTS	25½" & 34"	34" & 42½"
RISER WEIGHT WITH LEGS	29 lbs.	34 lbs.
RISER HANDRAIL WEIGHT	7.8 lbs.	9 lbs.
PLATFORM WEIGHT WITH LEGS	47 lbs.	47 lbs.
PLATFORM HANDRAIL WEIGHT	17 lbs.	17 lbs.
SYSTEM NET WEIGHT	101 lbs.	107 lbs.
FOOTPRINT (FULLY ASSEMBLED)	41" W x 89½" L x 76⅝" H	41" W x 99" L x 76⅝" H
PLATFORM SIZE - OVERALL	40" W x 60" L x 23" H	40" W x 60" L x 23" H
PLATFORM SIZE - USEABLE	36½" W x 56½" L	36½" W x 56½" L
ALUMINUM TYPE	6000 series	6000 series
RATED LOAD (DO NOT EXCEED RATED LOAD)	100 lbs. sq. ft., 300 lbs. concentrated	100 lbs. sq. ft., 300 lbs. concentrated
STANDARD FEET	4" x 4" sq.	4 x 4" sq.
OVERSIZED FEET (OPTIONAL) Anchor-ready polymer foot with thumb screw for tightening (anchors not included).	7⅝" x 7⅝" sq.	7⅝" x 7⅝" sq.
RISER HEIGHT	8½"	8½"
RISER TREAD DEPTH	9½"	9½"
RISER TREAD WIDTH	36½"	36½"
RISER HANDRAIL HEIGHT <i>Measured from leading edge of step tread to gripping surface</i>	36"	36"
PLATFORM HANDRAIL HEIGHT	42½"	42½"
WARRANTY	3-Year Limited	3-Year Limited
RISER TYPE	Open	Open
UNIVERSAL HANDRAILS	Left or right turn	Left or right turn

Weights and dimensions are approximate and subject to change.

FLOOR AND BUILDING ATTACHMENT	Anchor-ready angle braces on platform to secure to building (anchors not included).
OPTIONAL PLATFORM W/ DRAIN HOLES	3/8" x 3/4" holes on tread surface for draining of water build-up.



FORTRESS® OSHA Stair System

Technical Specifications

DRAWING DIMENSIONS ARE SHOWN IN INCHES

